



# GREAVES

## COMPRESSION

### Shoo-in™ FLEX-CABLE CONNECTORS

For flexible cable applications in locomotive, marine, mining, welding machinery, temporary power, wind power and transformers  
 Features flared Shoo-in™ barrel opening for easy cable insertion  
 Copper, tin-plated for corrosion resistance  
 Positive center stop

For copper cable  
 600 V\*\*

### SHORT BARREL SPLICES SC-FX SERIES



NAED NUMBER	CATALOG NUMBER	DIESEL-LOCOMOTIVE		CLASS H ROPE CABLE AWG/MCM	CLASS M WELD CABLE AWG/MCM	U-TYPE DIE		EST. SHIPPING	
		APPROX (AWG) MCM	CABLE STRAND			COLOR	INDEX	WEIGHT (lbs)	UNIT
32150	SC 50FX	(3) 50.3	125/24	#4	#4	GRAY	8	0.05	EA
32151	SC 60FX	(2) 60.6	150/24	#2	#2	BROWN	10	0.05	EA
32152	SC 90FX	(1) 90.9	225/24	#1	#1	GREEN	11/375	0.06	EA
32153	SC 111FX	(1/0) 111.1	275/24	1/0	#1/0	PINK	12/348	0.07	EA
32154	SC 131FX	(2/0) 131.3	325/24	2/0	-	BLACK	13	0.09	EA
32155	SC 181FX	(3/0) 181.8	450/24	3/0	#2/0	ORANGE	14	0.11	EA
32156	SC 222FX	(4/0) 222.2	550/24	4/0	#3/0	PURPLE	15	0.14	EA
32157	SC 262FX	262.6	650/24	250	#4/0	WHITE	17/298	0.15	EA
32158	SC 313FX	313.1	775/24	300	250	RED	18/324	0.22	EA
32161	SC 373FX	373.7	925/24	350	300	BLUE	19/470	0.32	EA
32159	SC 444FX	444.4	1100/24	400	350	BROWN	20/299	0.46	EA
32160	SC 535FX	535.3	1325/24	500	400	PINK	300	0.52	EA
32162	SC 646FX	646.4	1600/24	700	600	BLACK	24/473	0.60	EA

\*\*May be used for applications up to 35 KV when proper installation and insulation procedures are employed.



### LONG BARREL SPLICES C-FX SERIES



NAED NUMBER	CATALOG NUMBER	DIESEL-LOCOMOTIVE		CLASS H ROPE CABLE AWG/MCM	CLASS M WELD CABLE AWG/MCM	U-TYPE DIE		EST. SHIPPING	
		APPROX (AWG) MCM	CABLE STRAND			COLOR	INDEX	WEIGHT (lbs)	UNIT
32410	C 373FX	373.7	925/24	350	300	BLUE	19/470	0.55	EA
32420	C 444FX	444.4	1100/24	400	350	BROWN	20/299	0.65	EA
32430	C 535FX	535.5	1325/24	500	400	PINK	300	0.85	EA
32440	C 646FX	646.4	1600/24	700	600	BLACK	24/473	1.05	EA
32450	C 777FX	777.7	1925/24	800	700	YELLOW	936	1.45	EA

\*\*May be used for applications up to 35 KV when proper installation and insulation procedures are employed.  
 Due to the variety of styles of high-strand, flexible cable, and due to the variations among cable manufacturers, it is recommended to fit the conductor to the actual cable being utilized. (See Sizing Guide.)  
 For sizes not listed consult factory for availability.