



COMPRESSION

NECK-DOWN™ REDUCING SPLICES – COPPER


GREAVES EXCLUSIVE

Long barrel reducers to join copper wires of different sizes
 Produced from high-conductivity seamless copper tubing
 Marked with die index and die color code on each end
 Can be insulated with high heat-shrink tubing
 Also see CRK Series compression Reducer Kits

For copper cable only
 600V*

ND-R SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE		U-TYPE DIE A		U-TYPE DIE B	
		A	B	COLOR	INDEX	COLOR	INDEX
52012	ND 10R2	1/0	#2	PINK	12/348	BROWN	10
52011	ND 10R1		#1			GREEN	11/375
52021	ND 20R10	2/0	1/0	BLACK	13	PINK	12/348
52032	ND 30R20	3/0	2/0	ORANGE	14	BLACK	13
52042	ND 40R20	4/0	2/0			BLACK	13
52043	ND 40R30	4/0	3/0	PURPLE	15	ORANGE	14
52252	ND 250R20	250	2/0			BLACK	13
52254	ND 250R40	250	4/0	YELLOW	16	PURPLE	15
52302	ND 300R250	300	250	WHITE	17/298	YELLOW	16
52354	ND 350R40	350	4/0	RED	18/324	PURPLE	15
52352	ND 350R250	350	250	RED	18/324	YELLOW	16
52403	ND 400R350	400	350	BLUE	19/470	RED	18/324
52502	ND 500R250		250			RED	18/324
52503	ND 500R350	500	350	BLUE	19/470	RED	18/324
52504	ND 500R400		400			BLUE	19/470
52635	ND 600R350	600	350			GREEN	22/472
52650	ND 600R500	600	500	GREEN	22/472	BROWN	20/299
52755	ND 750R500	750	500			BROWN	20/299
52756	ND 750R600	750	600	BLACK	24/473	GREEN	22/472
52107	ND 1000R750	1000	750	WHITE	27	BLACK	24/473
52121	ND 1250R1000	1250	1000	YELLOW	29	WHITE	27
52151	ND 1500R1000	1500	1000	GREEN	31	WHITE	27
52162	ND 1500R1250	1500	1250	GREEN	31	YELLOW	29



*May be used for applications up to 35 KV when proper installation and insulation procedures are employed.
 Manufactured to order, consult factory for availability. Minimum order 3 pieces of same size.
 For tin plating add suffix "P" to Catalog No; adds approx. 1 week production time. Consult factory for combinations not listed.


ALUMINUM REDUCING SPLICES

Made of high conductivity wrought aluminum
 Long barrel with positive center stop to assure proper cable insertion
 Can be insulated with high heat-shrink tubing
 Connector bores are coated with oxide-inhibitor and capped

AC-R SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE		DIE A & B		EST. SHIPPING	
		A	B	COLOR	INDEX	WEIGHT(lbs)	UNIT
53012	AC 10R2	1/0	#2		BG, 8A, 5/8		EA
53021	AC 20R1	2/0	#1		60, 245	.15	EA
53031	AC 30R10	3/0	1/0		TU, 781, 56		EA
53042	AC 40R20	4/0	2/0		298, 840		EA
53253	AC 250R30	250	3/0		11A, 249, 840		EA
53304	AC 300R40	300	4/0			.21	EA
53354	AC 350R40	350	4/0	BROWN	96, 299		EA
53402	AC 400R250	400	250	GREEN	22, 472		EA
53530	AC 500R300	500	300			.77	EA
53535	AC 500R350	500	350	PINK	106, 300	.80	EA
53635	AC 600R350	600	350	BLACK	24, 473	1.15	EA
53750	AC 750R500	750	500	RED	140, 301	1.32	EA
53107	AC 1000R750	1000	750	BROWN	161, 302	1.90	EA

Dual-Rated
 CUAL
 600 V*



*May be used for applications up to 35KV when proper installation and insulation procedures are employed.
 Other sizes available, consult factory.
 Manufactured to order, consult factory for availability.