



## POWER DISTRIBUTION

### INSULATED MULTI-CABLE

Insulated with rugged high-dielectric rubber/vinyl coating  
 Saves installation time—no taping  
 Pre-filled with oxide-inhibitor  
 Easy re-entry for changes, inspection, or troubleshooting  
 Plugs marked with connector max wire size for easy identification  
 For flex/extra-flex high-strand wire, first install a PT-FX Shoo-Pin™ Adapter  
 6061-T6 high strength aluminum alloy  
 UL listed through 600MCM size  
 Copper wire only for #14-#6 AWG

**Dual-Rated**

90°C  
 CU9AL  
 600V



### USA SERIES

### One-Side Entry

NAED NUMBER	CATALOG NUMBER	WIRE PORTS	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY	EST. SHIPPING	
					LENGTH	HEIGHT		WEIGHT (lbs)	UNIT
13443	USA 4-3	3			1.54		12	1.30	CTN
13444	USA 4-4	4			1.97	1.45	6	0.89	CTN
13446	USA 4-6	6	#4 - 14	1/8	3.13		4	0.87	CTN
13448	USA 4-8	8			4.13		4	1.11	CTN
13453	USA 2-3	3			1.59		12	1.34	CTN
13454	USA 2-4	4			1.99	1.45	6	0.90	CTN
13456	USA 2-6	6	#2 - 14	5/32	2.87		4	0.90	CTN
13458	USA 2-8	8			3.69		4	1.13	CTN
13423	USA 2/0-3	3			2.34		6	1.21	CTN
13424	USA 2/0-4	4			3.01		6	1.53	CTN
13425	USA 2/0-5	5	2/0 - #14	7/32	3.69	1.50	4	1.23	CTN
13426	USA 2/0-6	6			4.36		4	1.44	CTN
13427	USA 2/0-7	7			4.74		3	1.28	CTN
13428	USA 2/0-8	8			5.41		3	1.48	CTN
13433	USA 3/0-3	3	3/0 - #6	1/4	2.65	1.86	6	1.50	CTN
13599	USA 250-3	3			2.99		4	1.51	CTN
13600	USA 250-4	4			3.85		4	2.09	CTN
13601	USA 250-5	5			4.71		3	1.96	CTN
13605	USA 250-6	6	250 - #6	5/16	5.57	2.10	3	2.33	CTN
13606	USA 250-7	7			6.43		2	1.91	CTN
13610	USA 250-8	8			7.29		2	2.01	CTN
13614	USA 350-3	3			3.52		4	2.43	CTN
13615	USA 350-4	4			4.57		3	2.54	CTN
13616	USA 350-5	5			5.62	2.50	3	3.12	CTN
13620	USA 350-6	6	350 - #6	5/16	6.67		2	2.44	CTN
13621	USA 350-7	7			7.72		2	2.74	CTN
13625	USA 350-8	8			8.77		2	3.30	CTN
13663	USA 600-3	3			4.89		3	3.02	CTN
13664	USA 600-4	4			5.63		2	2.15	CTN
13665	USA 600-5	5			7.11	2.90	2	3.30	CTN
13666	USA 600-6	6	600 - #4	5/16	8.47		2	3.89	CTN
13667	USA 600-7	7			9.83		2	4.43	CTN
13668	USA 600-8	8			11.18		2	5.26	CTN
13644	*USA 750-3	3			4.90		3	4.52	CTN
13645	*USA 750-4	4			6.19		1	1.41	EA
13646	*USA 750-5	5			7.75		1	2.61	EA
13650	*USA 750-6	6	750 - 250	5/16	9.18	3.60	1	3.04	EA
13651	*USA 750-7	7			10.60		1	3.44	EA
13655	*USA 750-8	8			12.03		1	3.91	EA

All wires enter same side



\* 750 MCM size not UL listed.



# GREAVES

## POWER DISTRIBUTION

### INSULATED MULTI-CABLE

Insulated with rugged high-dielectric rubber/vinyl coating  
 Saves installation time—no taping  
 Pre-filled with oxide-inhibitor  
 Easy re-entry for changes, inspection, or troubleshooting  
 Plugs marked with connector max wire size for easy identification  
 For flex/extra-flex high-strand wire, first install a PT-FX Shoo-Pin™ Adapter  
 6061-T6 high strength aluminum alloy  
 Copper wire only for #14-#6 AWG

**Dual-Rated**

90°C  
 CU9AL  
 600V



### USAD SERIES

### Optional-Side Entry

NAED NUMBER	CATALOG NUMBER	WIRE PORTS	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY	EST. SHIPPING				
					LENGTH	HEIGHT		WEIGHT (lbs)	UNIT			
13843	USAD 4-3	3			1.54		12	1.39	CTN			
13844	USAD 4-4	4	#4 - 14	1/8	1.97	1.45	6	0.91	CTN			
13846	USAD 4-6	6			3		0.91	CTN				
13848	USAD 4-8	8			3		0.99	CTN				
13853	USAD 2-3	3						1.59	12	1.43	CTN	
13854	USAD 2-4	4	#2 - 14	5/32	1.99	1.45	6	0.96	CTN			
13856	USAD 2-6	6			4		0.93	CTN				
13858	USAD 2-8	8			4		1.21	CTN				
13823	USAD 2/0-3	3						2.34	6	1.23	CTN	
13824	USAD 2/0-4	4	2/0 - #14	7/32	3.01	1.50	6	1.56	CTN			
13825	USAD 2/0-5	5			4		1.32	CTN				
13826	USAD 2/0-6	6			4		1.60	CTN				
13827	USAD 2/0-7	7			3		1.31	CTN				
13828	USAD 2/0-8	8			3		1.51	CTN				
13829	USAD 2/0-9	9			1		0.65	EA				
13830	USAD 2/0-10	10			1		0.85	EA				
13831	USAD 2/0-11	11			1		0.92	EA				
13832	USAD 2/0-12	12			1		1.00	EA				
13883	USAD 3/0-3	3			3/0 - #6		1/4	2.65	1.86	6	1.60	CTN
13884	USAD 3/0-4	4						6		2.21	CTN	
13899	USAD 250-3	3			250 - #6		5/16	2.99	2.10	4	1.61	CTN
13900	USAD 250-4	4	4	2.28		CTN						
13903	USAD 250-5	5	3	2.16		CTN						
13905	USAD 250-6	6	3	2.47		CTN						
13907	USAD 250-7	7	2	1.87		CTN						
13910	USAD 250-8	8	2	2.20		CTN						
13911	USAD 250-9	9	1	1.31		EA						
13908	USAD 250-10	10	1	1.50		EA						
13909	USAD 250-11	11	1	1.64		EA						
13912	USAD 250-12	12	1	1.89		EA						
13914	USAD 350-3	3	350 - #6	5/16		3.52		2.50		4	2.61	CTN
13915	USAD 350-4	4				3				2.76	CTN	
13918	USAD 350-5	5			3	3.31	CTN					
13920	USAD 350-6	6			2	2.69	CTN					
13922	USAD 350-7	7			2	3.00	CTN					
13925	USAD 350-8	8			2	3.36	CTN					
13926	USAD 350-9	9			1	2.08	EA					
13923	USAD 350-10	10			1	2.30	EA					
13924	USAD 350-11	11			1	2.34	EA					
13927	USAD 350-12	12			1	2.63	EA					
13963	USAD 600-3	3			600 - #4	5/16	4.39		2.90	3	3.36	CTN
13964	USAD 600-4	4					2			3.00	CTN	
13965	USAD 600-5	5	2	3.66			CTN					
13966	USAD 600-6	6	2	4.36			CTN					
13967	USAD 600-7	7	2	5.38			CTN					
13968	USAD 600-8	8	2	5.62			CTN					
13969	USAD 600-9	9	1	3.11			EA					
13970	USAD 600-10	10	1	3.66			EA					
13971	USAD 600-11	11	1	3.88			EA					
13972	USAD 600-12	12	1	4.28			EA					

Wire entry optional  
 from either side





## POWER DISTRIBUTION

### INSULATED MULTI-CABLE

Insulated with rugged high-dielectric rubber/vinyl coating  
 Saves installation time—no taping  
 Pre-filled with oxide-inhibitor  
 Easy re-entry for changes, inspection, or troubleshooting  
 Plugs marked with connector max wire size for easy identification  
 For flex/extra-flex high-strand wire, first install a PT-FX Shoo-Pin™ Adapter  
 6061-T6 high strength aluminum alloy

**Dual-Rated**

90°C  
 CU9AL  
 600V

### USAD SERIES

### Optional-Side Entry

NAED NUMBER	CATALOG NUMBER	WIRE PORTS	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY	EST. SHIPPING	
					LENGTH	HEIGHT		WEIGHT (lbs)	UNIT
13944	USAD 750-3	3			4.90		3	4.97	CTN
13945	USAD 750-4	4			6.19		1	2.21	EA
13948	USAD 750-5	5			7.75		1	2.66	EA
13950	USAD 750-6	6			9.18		1	3.26	EA
13952	USAD 750-7	7			10.60		1	3.69	EA
13955	USAD 750-8	8	750 - 250	5/16	12.03	3.60	1	4.23	EA
13956	USAD 750-9	9			13.46		1	4.68	EA
13953	USAD 750-10	10			14.88		1	5.11	EA
13954	USAD 750-11	11			16.30		1	5.56	EA
13957	USAD 750-12	12			17.73		1	5.91	EA

Wire entry optional  
 from either side



### SPARE PLUGS

Spare plugs for screw cover or wire ports  
 Marked with connector max wire size for easy identification

### PWS/PSP SERIES

NAED NUMBER	CATALOG NUMBER	CONN SIZE	CTN QTY	EST. SHIPPING	
				WEIGHT (lbs)	UNIT
<b>WIRE &amp; SCREW PORT</b>					
13724	PWS 4	#4	12	0.04	CTN
13722	PWS 2	#2	12	0.04	CTN
13720	PWS 2/0	2/0	12	0.06	CTN
13725	PWS 250	250	6	0.07	CTN
13735	PWS 350	350	6	0.08	CTN
13760	PWS 600	600	6	0.08	CTN
<b>WIRE PORT</b>					
13775	PWP 750	750	3	0.09	CTN
<b>SCREW PORT</b>					
13776	PSP 750	750	3	0.09	CTN

